

MODEL	2	F	5	B	8	8	N
DIGIT	1	2	3	4	5	6	7

REFRIGERANT TYPE
 1 = R12 (HERMETIC ONLY)
 2 = R22 (HERMETIC ONLY)
 3 = OPEN DRIVE

MODEL (TONS)				
CYL..	E		F	
	R-12	R-22	R-12	R-22
3	-	-	10	15
4	30	50	12.5	20
5	40	60	15	25
6	50	75	20	30
8	60	100	25	40

SPEED 5 = 1800 RPM

N	SOLENOID UNLOADING
W	100% UNLOADING (100% UNLOAD START)
R	RIGHT HAND
L	LOW LIFT VALVES
Z	REMOTE MOUNT ELECT. SOL. UNLOAD
Y	100% UNLOAD w/ REMOTE SOLENOID
X	NON UNLOADING COMPRESSOR

ELECTRICAL CHARACTERISTICS	
0	OPEN
1	460-3-60 SIX LEAD
2	575-3-60 SIX LEAD
7	440-3-60 SIX LEAD
8	200/230/460/-3-60 NINE LEAD
9	480-3-60 SIX LEAD

NUMBER OF CYLINDERS 3, 4, 5, 6 OR 8

DESIGN SEQUENCE A, B, C, D